

Serial No. 10/729,289

Amendments to the Specification

Please replace paragraph on page 8, beginning with line 1 with the following amended paragraph:

Such vehicle structure may include the curved or projecting rim 20 of a vehicle fender 21 facing the wheel well, and structure 22 such as a shock absorber or absorbers ~~23~~ 230, and/or a strut or struts or a tie rod or tie rods 24.

Please replace paragraph on page 8, beginning with line 16 with the following amended paragraph:

The assembly includes a first carrier 26 supporting the first gauge 13 for linear adjustable movement in direction or directions 23, and a second and transverse carrier 27 supporting the second gauge 15 for linear adjustable movement in a second direction ~~24~~ 17. Carrier 26 is carried by mount 50 and carrier 27 is or may be carried by gauge 13, as shown. The assembly may also include a third carrier 28 carried by ~~14~~ 13 and supporting the third gauge 18 for linear adjustable movement in third direction or directions ~~35~~ 25. Carrier 28 is supported by vertical slide 38, slidable in a carrier 39 attached to 26, but not to 27. The carriers may be elongated as shown, and have like sides 30, 31 and 32, gauge edge guides 33, 34 and 35,

Serial No. 10/729,289


and set screws ~~60~~ 160 to clamp edge guides, and that may be loosened to allow gauge adjustment and tightening, to fix the gauges in selected positions. The carriers are operatively interconnected.

Please replace paragraph on page 10, beginning with line 1 with the following amended paragraph:

Bolts 60 project from hub or mount ~~51~~ 151 for attachment to the wheel 52, or to the connector plate 50.

Serial No.10/729,289

Respectfully submitted,


William W. Haefliger
Attorney for Applicants
Registration No.17,120
Area Code 323 684-2707

WWH:hk

Docket 12,559